

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 June 2004 (24.06.2004)


PCT

(10) International Publication Number  
WO 2004/053433 A1

- (51) International Patent Classification<sup>7</sup>: G01F 19/00, 11/26, B65D 41/26, A61J 7/00
- (21) International Application Number: PCT/GB2003/005318
- (22) International Filing Date: 5 December 2003 (05.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0228480.0 6 December 2002 (06.12.2002) GB
- (71) Applicant (for all designated States except US): **BOOTS HEALTHCARE INTERNATIONAL LIMITED** [GB/GB]; 1 Thane Road West, Nottingham NG2 3AA (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **PERRY, Timothy** [GB/GB]; 55 Bedford Road, London W13 0SP (GB).
- (74) Agents: **PIDGEON, Robert, John et al.**; Appleyard Lees, 15 Clare Road, Halifax HX1 2HY (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: MEASURING AND DISPENSING DEVICE FOR ATTACHMENT TO THE CAP ON A BOTTLE



(57) Abstract: A measuring and dispensing device (2) for attachment to the cap (14) of a bottle (16) of liquid medicine comprises on one of its sides a socket formation (6), by means of which it may be releasably attached to the cap, and on another side a concave formation (4) for receiving liquid medicine.

WO 2004/053433 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## MEASURING AND DISPENSING DEVICE FOR ATTACHMENT TO THE CAP ON A BOTTLE

The present invention relates to a device for measuring and dispensing liquid medicine.

5

One current device for measuring and dispensing liquid medicine is a graduated medicine spoon. This is cheap and compact but many users find it prone to spillage, and inconvenient to use.

10

A second measuring and dispensing device is a graduated cup. This is typically a substantially straight-sided cup with a transverse bottom wall. This is less prone to mess than the spoon but is prone to difficulties, nevertheless.

15

The straight-sided design means that it can be difficult to accurately assess the level of liquid against the graduations. Furthermore, there may be a considerable loss of viscous liquid medicines, retained on the inside surfaces of the cup. With the spoon, of course, the user typically uses the mouth parts to remove all the medicine. With the cup the user only receives the medicine which flows under gravity into the mouth.

20

In accordance with the present invention there is provided a measuring and dispensing device for attachment to the cap on a bottle of liquid medicine, the device comprising on one of its sides a socket formation by means of which it may be releasably attached to the cap, and on another side a concave formation for receiving liquid medicine.

25

30

Preferably the socket formation and the concave formation face in opposite directions. In use, with the bottle still on its base, the socket formation faces downwards

and the concave formation faces upwards, with the device being carried at the top of the bottle.

Preferably the concave formation and the socket formation  
5 are the only recess formations in the device.

The device could be positively secured to the cap, for example by means of a screw connection, between the internal surface of the socket and the external surface of  
10 the cap. Preferably, however, there is no such positive securement. Preferably there is only a drop-on connection between the socket and the bottle cap. Preferably removal of the device from the bottle merely requires the device to be lifted from the bottle, so that the socket is raised  
15 from the cap.

Preferably the cap of the bottle fits reasonably closely within the socket, sufficiently closely that the device cannot easily be knocked from the cap of the bottle but  
20 not so closely that the measuring and dispensing device can be used to assist the removal of the cap. If this happened it would compromise any child-resistant property of the cap of the bottle.

25 However, embodiments in which the measuring and dispensing device is secured to a cap of the bottle in such a way that they can be turned together are not excluded. Such embodiments may be employed when it is desired to provide some assistance to overcome any child-resistance features,  
30 with the measuring and dispensing device providing a mechanical advantage, compared with the cap alone. Such assistance may be required by elderly persons, for example.

- Preferably the measuring and dispensing device, when removed from the bottle, may be stood on a horizontal surface with the concave formation facing upwards, so that liquid medicine can be poured into it. One way in which this can be achieved is by the termination of the free end of the socket formation in a plain edge. Preferably such an edge is circular and all in one plane, substantially perpendicular to the axis of the socket formation.
- 10 Another embodiment has a plurality of feet all terminating in a common plane. For stability there are preferably at least three feet, preferably evenly spaced about the free end of the socket formation. In such an embodiment there is preferably an even number of feet. By such means the user can hold the device in a very stable manner, with 15 finger and thumb applied across a diameter of the socket formation, from one foot to another. When there is an odd number of feet the device cannot be held so securely, from foot to foot across a diameter.
- 20 Preferably the measuring and dispensing device is of a plastics material, more preferably a thermoplastics material. Especially suitable are polyolefins, for example polyethylene or, most preferably, polypropylene.
- 25 Preferably the measuring and dispensing device is manufactured by a moulding process, for example injection moulding.
- 30 Preferably the internal surface of the concave formation is graduated, most preferably with 2.5ml and/or 5ml graduations. Alternatively or additionally it may have a 10ml graduation and/or a 15ml graduation. Preferably the

capacity of the concave formation is somewhat larger than the volume denoted by the highest graduation, so that, for a corresponding dose, it does not have to be filled to the top. Preferably its capacity is at least 8ml.  
5 Preferably, its capacity does not exceed 25ml, and preferably does not exceed 15ml. Most preferably it does not exceed 12ml.

Suitably the concave formation is circular, or,  
10 preferably, oval in plan view.

In certain embodiments the concave formation is without discontinuities on its internal surface. For example it contains no bumps, ridges or grooves marking the  
15 transition between one region of the surface and another, but preferably curves smoothly throughout its internal surface. In such embodiments any graduation is by means of in-the-plane surface marking, for example achieved by co-injection moulding.

20

In other embodiments any graduation is by means of one or more surface discontinuities, preferably one or more ridges. When such is provided the concave formation is otherwise free of discontinuities on its internal surface.

25

Preferably the internal surface of the concave formation has a surface finish which does not tend to retain liquid medicine. For example the surface may by its chemical nature repel the liquid medicine. Alternatively, it may  
30 have a physical finish which has a similar effect. For example it may have a surface which is microscopically smooth. The surface may have a shiny finish, preferably

achieved by the method of primary manufacture, for example by employing a highly polished mould.

The concave formation may terminate, at its rim, in a slightly inwardly displaced region, with a view to preventing some incidents of spillage of liquid medicine, from the concave formation.

The upper face within the socket formation could be flat but is preferably concave, uneven or, especially convex, so that the top of the cap of the bottle and the upper surface of the socket formation do not make substantial face-to-face contact. Preferably the upper face of the socket formation follows the shape of the concave formation. Preferably there is a curved wall therebetween, having the respective concave and convex surfaces.

Preferably the upper face within the socket formation has one or more projections, preferably including at least a central projection when the upper face is concave. This means that there is only point contact between the upper face with the socket formation and the top of the cap. We have found that this measure facilitates the removal of the dispensing and measuring device from the bottle cap.

In accordance with a second aspect of the present invention there is provided a bottle of liquid medicine, the cap of the bottle having fitted to it a measuring and dispensing device of the first aspect, as defined above.

In accordance with a third aspect of the present invention there is provided a method of dispensing liquid medicine

from the bottle of the second aspect, the method including:

removing the measuring and dispensing device from the cap  
5 of the bottle;

removing the cap; and

delivering the liquid medicine from the bottle into the  
10 concave formation of the measuring and dispensing device  
to the required amount.

The invention will now be further described, by way of  
example, with reference to the accompanying drawings, in  
15 which:

Fig. 1 shows a first embodiment of measuring and  
dispensing device of the present invention in side  
elevation;

20

Fig. 2 shows the same device in front elevation;

Fig. 3 shows the same device in plan view;

25 Fig. 4 is a sectional view of the device along line X-X in  
Fig. 3;

Fig. 5 is a sectional view of the same device along line  
Y-Y in Fig. 3;

30

Fig. 6 shows the same device mounted on a bottle of liquid  
medicine, the bottle being shown in outline; and



Fig. 7 shows a second embodiment of measuring and dispensing device of the invention in side view.

The measuring and dispensing device 2 has on one side a concave formation 4 and has on its other side a socket formation 6. The socket formation 6 is generally cylindrical. The concave formation 4 is smoothly concave, without any surface discontinuities. It is in the form of a dish or bowl, of volume 12ml. In plan view it is of oval shape, as can be seen in Fig. 3.

The measuring and dispensing device is made by injection moulding of polypropylene. The surface finish is very smooth and shiny and this is achieved by virtue of the material selected and the very smooth finish of the cavity of the mould employed in the manufacture.

On the internal surface of the concave formation there are in-the-plane graduation lines 8 and numbers indicative of 2.5ml and 5ml liquid volume levels. These are formed by co-injection during the moulding process.

The concave formation 4 is moulded at its rim with a inflect 9, as an anti-spill measure.

The cylindrical wall of the socket formation terminates at its free end in a deep wavy edge 10, this edge defining four identical feet 12 with equal spaces between them.

The socket formation 6 is of size to fit snugly over the cylindrical cap 14 which closes the neck of medicine bottle 16, so that there is little risk of the device falling from, and little risk of it being knocked from,

the cap. Removal of the device requires a linear lifting action. However there is no grip between the socket formation 6 and the cap 14 so the latter cannot be used as an aid for the removal of the cap from the bottle. Thus, 5 the child-resistance of the cap is not compromised.

The upper face 18 of the socket formation 6 is convex, corresponding to the shape of the concave formation; the shape of both being defined by a common, curved, wall 20. 10 The convex upper surface 18 is formed at its peak with a small pip-like projection 22. The projection 22 marks the site of mould-filling. In the finished device it is left. When the device is pushed onto the bottle cap the contact between the concave formation and the top of the cap is, 15 substantially, point contact, not surface-to-surface contact. This may facilitate removal of the device.

To measure and dispense medicine the device 2 is first lifted from the cap. The cap 14 is then removed from the 20 bottle 16 in the usual way. Liquid medicine is poured from the bottle 16 into the concave formation of the device. During this operation the device may be resting on a horizontal surface, for example a worktop. Alternatively, if the user has a steady hand and prefers 25 it, it may be held. Once the liquid has reached the required graduation line it may be placed against and poured into the mouth. Very little liquid medicine should be left in the concave formation and so nothing further is necessary. However if the user does choose to remove any 30 remaining liquid medicine from the surface of the concave formation using mouth parts, for example the upper lip or tongue, this is easy to do.

The bottle 16 is shown with a special shape but this is not material to the present invention. A bottle of any shape could be used, and of any suitable material, for example glass or plastics.

5

The second embodiment of measuring and dispensing shown in Fig. 7 is the same as the first embodiment except that it has three feet 12A, not four.

10 In a third embodiment (not shown) the socket formation ends in a plain edge which is perpendicular to the axis of the socket formation.

In a fourth embodiment (not shown) the concave formation  
15 is circular in plan view.

In a fifth embodiment (not shown) the two in-the-plane graduation lines are absent, and instead there are two moulded-in ridges.

20

CLAIMS

1. A measuring and dispensing device for attachment to the cap on a bottle of liquid medicine, the device comprising on one of its sides a socket formation by means of which it may be releasably attached to the cap, and on another side a concave formation for receiving liquid medicine.
2. A device as claimed in claim 1, wherein the socket formation and the concave formation face in opposite directions.
3. A device as claimed in claim 1 or 2, wherein the device is stable when the socket formation rests on a horizontal surface.
4. A device as claimed in any preceding claim, wherein the concave formation is graduated on its internal surface.
5. A device as claimed in any preceding claim, wherein the internal surface of the concave formation has a surface finish which does not act to retain liquid medicine.
6. A bottle of liquid medicine, having a cap onto which is fitted the socket formation of a measuring and dispensing device as claimed in any preceding claim.

7. A bottle as claimed in claim 6, wherein the socket formation is a close but non-gripping fit on the cap.

5 8. A method of dispensing liquid medicine from a bottle as claimed in claim 6 or 7, the method including:

10 removing the measuring and dispensing device from the cap of the bottle;

removing the cap of the bottle; and

15 delivering the liquid medicine from the bottle into concave formation of the measuring and dispensing device to the required amount.

20 9. A measuring and dispensing device, or a bottle or method using same, substantially as hereinbefore described with reference to the accompanying drawings.

1/3

FIG. 1




FIG. 2





FIG. 3



2/3

FIG. 4




FIG. 5






FIG. 7



3/3

FIG. 6





## INTERNATIONAL SEARCH REPORT

Intern. Application No  
PCT/GB 03/05318

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01F19/00 G01F11/26 B65D41/26 A61J7/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01F B65D A61J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	ES 276 900 U (CAMP FABRICA DE JABONES) 16 June 1984 (1984-06-16) the whole document	1-9
Y	DE 83 33 126 U (TAD PHARM WERK) 2 February 1984 (1984-02-02) page 10, paragraph 3; figure 3	1-9
A	US 202 268 A (WILMER KELLER) 9 April 1878 (1878-04-09) page 1, right-hand column; figures 1,2	4,5
A	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 24, 11 May 2001 (2001-05-11) -& JP 2001 192038 A (BANDAI CO LTD), 17 July 2001 (2001-07-17) abstract; figures 5-7	7
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is, taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*G\* document member of the same patent family

Date of the actual completion of the international search

16 April 2004

Date of mailing of the international search report

27/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Roetsch, P

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 03/05318

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 150 761 A (COLLINS HERBERT) 24 April 1979 (1979-04-24) the whole document ----	1-9
A	US 2 559 168 A (WILLIAM NUMBERS) 3 July 1951 (1951-07-03) column 2, line 17 -column 3, line 7 column 4, line 15-28 figures 1,5 ----	1-9
A	US 2 019 071 A (CARR FRANK P) 29 October 1935 (1935-10-29) the whole document ----	1-9
A	DE 567 569 C (WILHELM HERUSCH) 23 September 1933 (1933-09-23) the whole document -----	1-9

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/05318

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
ES 276900	U	16-06-1984	NONE	
DE 8333126	U	02-02-1984	DE 8333126 U1	02-02-1984
US 202268	A		NONE	
JP 2001192038	A	17-07-2001	NONE	
US 4150761	A	24-04-1979	AU 519934 B2	07-01-1982
			AU 3145677 A	21-06-1979
			BE 862183 A1	14-04-1978
			CA 1083532 A1	12-08-1980
			CH 617145 A5	14-05-1980
			DE 2759098 A1	01-02-1979
			GB 1593066 A	15-07-1981
			JP 54019886 A	14-02-1979
			NZ 186109 A	24-04-1981
			PH 15960 A	04-05-1983
			ZA 7707521 A	25-10-1978
US 2559168	A	03-07-1951	NONE	
US 2019071	A	29-10-1935	NONE	
DE 567569	C	23-09-1933	NONE	

